

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A field emission display, comprising:
a first substrate and a second substrate opposing one another with a ~~predetermined~~ gap therebetween, the first substrate and the second substrate being sealed using a sealant wherein a vacuum ~~assembly is formed between the first substrate and the second substrate forms a vacuum assembly in an area a region~~ encompassed by the sealant;
an electron emission assembly ~~formed located~~ on the first substrate ~~and for~~ emitting electrons by generation of electric fields within the electron emission assembly; and
an illumination assembly ~~formed located~~ on the second substrate ~~and for~~ realizing a display of images by electrons emitted from the electron emission assembly,
wherein the illumination assembly includes (a) a transparent conductive layer ~~formed located~~ on a surface of the second substrate, the transparent conductive layer having a portion extending beyond the sealant as an anode input terminal to which an anode voltage is applied, (b) a phosphor screen ~~formed located~~ on the transparent conductive layer, and (c) a metal layer ~~formed located~~ on the phosphor screen within the vacuum assembly, a portion of the metal layer contacting and electrically ~~connecting connected~~ to the transparent conductive layer.
2. (original) The field emission display of claim 1, wherein the transparent conductive layer and the anode input terminal are integrally formed.
3. (original) The field emission display of claim 2, wherein the transparent conductive layer and the anode input terminal are made of films of indium tin oxide.

4. (original) The field emission display of claim 1, wherein the metal layer is formed over the phosphor screen having an area larger than the phosphor screen such that edges of the metal layer contact the transparent conductive layer.

5. (original) The field emission display of claim 1,
wherein the electron emission assembly includes electron emission sources and electrodes for inducing the emission of electrons from the electron emission sources, and
wherein the electrodes include cathode electrodes and gate electrodes insulated from each other by an insulation layer and formed in respective stripe patterns, the cathode electrodes being substantially perpendicular to the gate electrodes.

6. (original) The field emission display of claim 5, wherein the electron emission sources are made of a carbon-based material selected from a group consisting of carbon nanotubes, graphite, diamond, diamond-like carbon, C₆₀ (Fullerene), or a combination of these materials.

7. (original) The field emission display of claim 5, further comprising the gate electrodes being formed on the first substrate, the insulation layer being formed on the first substrate covering the gate electrodes, the cathode electrodes being formed on the insulation layer, and the electron emission sources being formed on the cathode electrodes.

8. (original) The field emission display of claim 5, further comprising the cathode electrodes being formed on the first substrate, the insulation layer being formed on the first substrate covering the cathode electrodes, the gate electrodes being formed on the insulation layer, the insulation layer and the gate electrodes including openings for exposing the cathode electrodes, and the electron emission sources being formed in the openings on the exposed cathode electrodes.

9. (currently amended) A field emission display, comprising:

a first substrate and a second substrate opposing one another with a ~~predetermined~~ gap therebetween, the first substrate and the second substrate being sealed using a sealant wherein a vacuum ~~assembly is~~ formed between the first substrate and ~~the~~ second substrate ~~forms a vacuum assembly in an area a region~~ encompassed by the sealant;

an electron emission assembly ~~formed~~ located on the first substrate ~~and for~~ emitting electrons by generation of electric fields within the electron emission assembly; and

an illumination assembly ~~formed~~ located on the second substrate ~~and for~~ realizing a display of images by electrons emitted from the electron emission assembly,

wherein the illumination assembly includes a phosphor screen ~~formed~~ located on a first surface of the second substrate, a metal layer ~~formed~~ located on the phosphor screen within the vacuum assembly, and an anode input terminal ~~formed~~ extending from within the vacuum assembly to outside of the sealant, in which an end of the anode input terminal within the vacuum assembly contacts both the phosphor screen and the metal layer ~~to be electrically connected to the metal layer~~ and ~~an anode voltage is applicable to~~ a portion of the anode input terminal extending beyond the sealant is configured to receive an anode voltage.

10. (original) The field emission display of claim 9, wherein the anode input terminal is a thin film made from a material selected from a group consisting of indium tin oxide, Ni, and Cr.

11. (original) The field emission display of claim 9, wherein the metal layer covers entirely the phosphor screen and a portion of the anode input terminal.

12. (previously presented) The field emission display of claim 9,
wherein the electron emission assembly includes electron emission sources and electrodes for inducing emission of electrons from the electron emission sources, and

wherein the electrodes include cathode electrodes and gate electrodes, the cathode electrodes and the gate electrodes being insulated from each other by an insulation layer and formed respectively in a stripe pattern, the cathode electrodes being substantially perpendicular to the gate electrodes.

13. (original) The field emission display of claim 12, wherein the electron emission sources are made of a carbon-based material selected from a group consisting of carbon nanotubes, graphite, diamond, diamond-like carbon, C₆₀ (Fullerene), or a combination of these materials.

14. (original) The field emission display of claim 12, further comprising the gate electrodes being formed on the first substrate, the insulation layer being formed on the first substrate covering the gate electrodes, the cathode electrodes being formed on the insulation layer, and the electron emission sources being formed on the cathode electrodes.

15. (original) The field emission display of claim 12, further comprising the cathode electrodes being formed on the first substrate, the insulation layer being formed on the first substrate covering the cathode electrodes, the gate electrodes being formed on the insulation layer, the insulation layer and the gate electrodes including openings for exposing the cathode electrodes, and the electron emission sources being formed in the openings on the exposed cathode electrodes.

16. (currently amended) A flat panel display, comprising:
a faceplate ~~including~~ having a faceplate interior side;
a backplate ~~including~~ having a backplate interior side in an opposing relationship to the faceplate interior side;

~~side-walls~~ sidewalls positioned between the faceplate and the backplate to form an enclosed vacuum envelope between the ~~side-walls~~ sidewalls, the backplate interior side and the faceplate interior side;

a phosphor layer positioned on the faceplate interior side;

a transparent conductive layer located between the faceplate and the phosphor layer;

a metal layer positioned on the phosphor layer,

~~wherein:~~

wherein the metal layer is ~~formed~~ located entirely within the vacuum envelope[[:]]_and

wherein the transparent conductive layer includes an anode input terminal ~~extends~~
extending from within the vacuum envelope to outside the sidewalls.

17. (original) The flat panel display of claim 16, wherein the metal layer has a larger area than the phosphor layer.

18. (previously presented) The flat panel display of claim 16, wherein the metal layer contacts the anode input terminal within the vacuum envelope and an anode voltage is applied to the anode input terminal outside the sidewalls.

19. (canceled)

20. (canceled)

21. (canceled)

22. (canceled)

23. (currently amended) An illumination assembly for a field emission display realizing a display of images by electrons emitted from an electron emission assembly within a vacuum assembly between substrates sealed by a sealant, comprising:

a substrate;

a transparent conductive layer ~~formed~~ located on a surface of the substrate, the transparent conductive layer having a portion extending beyond the sealant and having an anode input terminal as a portion of the transparent conductive layer extending beyond the sealant to which an anode voltage is applied;

a phosphor screen ~~formed~~ located on the transparent conductive layer; and

a metal layer ~~formed~~ located on the phosphor screen, and having a portion of the metal layer for contacting and electrically connecting to the transparent conductive layer within the vacuum assembly.

24. (original) The illumination assembly of claim 23, wherein the transparent conductive layer and the anode input terminal are integrally formed.

25. (original) The illumination assembly of claim 23, wherein the metal layer is formed over the phosphor screen having an area larger than the phosphor screen such that edges of the metal layer contact the transparent conductive layer.